



ENVIRONMENTAL PRODUCT DECLARATION

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025 / ISO 21930

Ventilplus Light 14/2
Sicilferro Torrenovese SRL



EPD HUB, HUB-1115

Publishing on 15.02.2024, last updated on 15.02.2024, valid until 15.02.2029.

GENERAL INFORMATION

MANUFACTURER

Manufacturer	Sicilferro Torrenovese SRL
Address	Via Pietra di Roma, SNC
Contact details	info@sicilferro.it
Website	https://scfssystem.it/

EPD STANDARDS, SCOPE AND VERIFICATION

Program operator	EPD Hub, hub@epdhub.com
Reference standard	EN 15804+A2:2019 and ISO 14025
PCR	EPD Hub Core PCR version 1.0, 1 Feb 2022 EN 16783 Thermal insulation products
Sector	Construction product
Category of EPD	Third party verified EPD
Scope of the EPD	Cradle to gate with options, A5, and modules C1-C4, D
EPD author	Mauro Scurria
EPD verification	Independent verification of this EPD and data, according to ISO 14025: ☐ Internal certification ☒ External verification
EPD verifier	Haiha Nguyen, as an authorized verifier acting for EPD Hub Limited

The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804 and if they are not compared in a building context.

PRODUCT

Product name	Ventilplus Light 14/2
Additional labels	STD, CAM, ECO30, ECO100+
Product reference	VTL14/2
Place of production	Torrenova (ME) - Italy
Period for data	2022
Averaging in EPD	No averaging
Variation in GWP-fossil for A1-A3	< 41 %

ENVIRONMENTAL DATA SUMMARY

Declared unit	1 m ² (R-Value = 4,62 m ² K / W)
Declared unit mass	6 kg
GWP-fossil, A1-A3 (kgCO ₂ e)	2,54E+01
GWP-total, A1-A3 (kgCO ₂ e)	2,55E+01
Secondary material, inputs (%)	33.5
Secondary material, outputs (%)	82.6
Total energy use, A1-A3 (kWh)	93.6
Total water use, A1-A3 (m ³ e)	3,73E-01

PRODUCT AND MANUFACTURER

ABOUT THE MANUFACTURER

Sicilferro Torrenovese SRL was founded in 1982, in Torrenova, along the northern coast of Sicily. Operating in the construction sector for two generations with an approach focused on the offer of innovative construction solutions, in 1998 the company started a new division, the SCF Sistemi Costruttivi Futuri with the industrial intent of proposing on the market a leading company in the EPS construction products sector. SCF developed EPS slabs, sheet, wall and ventilated crawlspace. The company is certified in according to UNI EN 1090-2:2018, UNI EN ISO 3834-1:2021, UNI EN ISO 9001:2015, UNI EN ISO 14001:2015, PAS 2060 Carbon Neutrality.

PRODUCT DESCRIPTION

Insulating panel in Expanded Polystyrene (EPS) with variable geometry, reinforced and continuously co-sintered with two flat sheet of galvanized steel which give it particular characteristics of resistance. Usable for thermal insulation of the roof of civil and industrial buildings; thanks to its innovative and exclusive design, the incorporated foils can protrude by 2 cm from the extrados, allowing the creation of a microventilation chamber between the insulating mass and the upper finishing layer which improves the thermal-insulating quality of the system. Furthermore, the metal sheets embedded in the panel allow for a solid and rapid fixing of the secondary structures of the pitched roofing systems. Supplied with CE mark according to UNI EN 13163:2017. Ventilplus panel can be supplied in the version that meets the Minimum Environmental Criteria (C.A.M.) according to the D.M. 23/06/2022. The insulating panel covered by the following LCA is the Ventilplus Light 14/2, with a thick of 14 cm and protrude by 2 cm from the extrados.

RECYCLED MATERIAL IN THE PRODUCT

The insulating panel Ventilplus is made up of two types of materials, EPS and steel. In the following LCA analysis, virgin Expandable Polystyrene was considered, which does not contain any recycled material. As regards the galvanized steel of which the two sheets embedded inside the EPS are composed, coming entirely from an electric arc furnace (EAF), the declarations and assertions of the suppliers are considered, which gives an average percentage of recycled material inside the Ventilplus of approximately 33% by weight. The Ventilplus panel can be supplied with % recycled material in according to the D.M. 23/06/2022 (C.A.M.) foreseen Green Public Procurement (G.P.P.) with 15% of recycled material. Furthermore, the products are available with 33% recycled material in the ECO30 version or with 100% recycled material in the ECO100+ version, using EPS sourced from renewable feedstock certified.

LCA INFORMATION

This LCA complies with the regulations EN 16783:2017 Thermal insulation products - Product category rules (PCR) for factory made and in-situ formed products for preparing environmental product declarations. This LCA study includes the provision of all materials, transportation, energy and emission flows, and end of life processing of product. The use phase is not covered, assuming there are no use emissions or replacements. For easier modelling and because of lack of accuracy in available modelling resources, some constituents under 1% of product mass are excluded. These include some materials which are used in the product manufacturing only in very small amounts and have a negligible impact on the emissions of the product, for example grease and lubricating oil consumed at plant.

The production of capital equipment, construction activities, and infrastructure, maintenance and operation of capital equipment, personnel-related activities, energy and water use related to company management and sales activities are excluded.

Further information can be found at <https://scfssystem.it/>.

PRODUCT RAW MATERIAL MAIN COMPOSITION

Raw material category	Amount, mass- %	Material origin
Metals	54	Europe
Minerals	-	-
Fossil materials	46	Europe
Bio-based materials	-	-

BIOGENIC CARBON CONTENT

Product's biogenic carbon content at the factory gate

Biogenic carbon content in product, kg C	-
Biogenic carbon content in packaging, kg C	-

FUNCTIONAL UNIT AND SERVICE LIFE

Declared unit	1 m ² (R-Value = 4,62 m ² K/W)
Mass per declared unit	6 kg
Functional unit	-
Reference service life	-

SUBSTANCES, REACH - VERY HIGH CONCERN

The product does not contain any REACH SVHC substances in amounts greater than 0,1 % (1000 ppm).



PRODUCT LIFE-CYCLE

SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

Product stage			Assembly stage		Use stage							End of life stage				Beyond the system boundaries		
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D		
x	x	x	MND	x	MND	MND	MND	MND	MND	MND	MND	x	x	x	x	x		
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction	Transport	Waste processing	Disposal	Reuse	Recovery	Recycling

Modules not declared = MND. Modules not relevant = MNR.

MANUFACTURING AND PACKAGING (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production as well as packaging materials and other ancillary materials. Also, fuels used by machines, and handling of waste formed in the production processes at the manufacturing facilities are included in this stage. The study also considers the material losses occurring during the manufacturing processes as well as losses during electricity transmission.

The raw materials are expandable polystyrene and sheet of galvanized deep steel. The process begins with the pre-expansion of the expandable polystyrene granules using steam produced by boilers. The pre-expanded granules are stored in silos for seasoning. The galvanized sheet metal is drilled with circular section holes in order to lighten them without however compromising the structural characteristics. During this phase we have a production loss of approximately 9,6% in weight due to waste from the drilling process, which is entirely recovered for recycling. Metal scraps are collected and sent to a waste facility located 200 km from the

manufacturing site for recycling. Last step is the moulding phase, through which the specially shaped galvanized steel sheets are incorporated inside the panel. Each EPS panel is customized according to project requests. No packaging materials are used as the materials are supplied without.

TRANSPORT AND INSTALLATION (A4-A5)

Transportation impacts occurred from final products delivery to construction site (A4) cover fuel direct exhaust emissions, environmental impacts of fuel production, as well as related infrastructure emissions.

The transportation phase is not object of the analysis. In the assembly stage there is no request for materials.

PRODUCT USE AND MAINTENANCE (B1-B7)


This EPD does not cover the use phase.

Air, soil, and water impacts during the use phase have not been studied.

PRODUCT END OF LIFE (C1-C4, D)

Demolition is assumed to consume 0,01 kWh/kg of product. The source of energy is diesel fuel used by construction machines (C1). The distance for transportation to disposal is assumed as 200 km and the transportation method is assumed to be lorry (C2). The EOL of EPS is assumed to be incinerated by 80% and by 20% landfilled waste without reuse, recovery or recycling, according to the AIPE (Italian Expanded Polystyrene Association). Approximately 85% of steel is assumed to be recycled based on World Steel Association; it is assumed that the remaining 15% of steel is taken to landfill for final disposal (C3,C4). Module D includes the benefits due to the EPS incineration and steel recycling.

MANUFACTURING PROCESS AND SYSTEM BOUNDARY



LIFE-CYCLE ASSESSMENT

CUT-OFF CRITERIA

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. The study includes all major raw material and energy consumption. All inputs and outputs of the unit processes, for which data is available for, are included in the calculation. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

ALLOCATION, ESTIMATES AND ASSUMPTIONS

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, allocation has been done in the following ways:

Data type	Allocation
Raw materials	No allocation
Packaging materials	Not applicable
Ancillary materials	Allocated by mass or volume
Manufacturing energy and waste	Allocated by mass or volume

AVERAGES AND VARIABILITY

Type of average	No averaging
Averaging method	Not applicable
Variation in GWP-fossil for A1-A3	< 41 %

This EPD is product and factory specific and does not contain average calculations.

LCA has been done for the other 13 product variations in the Ventiplus Light, 5 product variations in the Ventilplus Medium, and 8 product variations in the Ventiplus Strong family. The results show that the GWP-fossil of the Product stage (A1-A3) of all the product variations does not exceed 41% of magnitude of Ventilplus Light 14/2's.

LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA EPD Generator. The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. Ecoinvent v3.8 and One Click LCA databases were used as sources of environmental data.

ENVIRONMENTAL IMPACT DATA

CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP – total ¹⁾	kg CO ₂ e	2,11E+01	1,23E+00	3,14E+00	2,55E+01	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	2,22E-02	2,57E-01	7,11E+00	8,88E-02	-7,55E+00
GWP – fossil	kg CO ₂ e	2,10E+01	1,23E+00	3,13E+00	2,54E+01	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	2,22E-02	2,57E-01	7,11E+00	8,88E-02	-7,53E+00
GWP – biogenic	kg CO ₂ e	7,28E-02	4,73E-04	4,13E-03	7,74E-02	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	4,07E-06	1,16E-04	3,60E-04	5,05E-05	-1,99E-02
GWP – LULUC	kg CO ₂ e	1,30E-02	5,15E-04	2,79E-04	1,38E-02	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	2,21E-06	1,21E-04	1,03E-04	8,68E-06	-1,23E-03
Ozone depletion pot.	kg CFC ₁₁ e	9,72E-07	2,81E-07	6,36E-07	1,89E-06	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	4,75E-09	5,78E-08	1,32E-08	2,81E-09	-4,54E-07
Acidification potential	mol H ⁺ e	4,28E-01	8,38E-03	2,42E-02	4,60E-01	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	2,31E-04	1,02E-03	1,65E-03	7,50E-05	-4,72E-02
EP-freshwater ²⁾	kg Pe	7,71E-04	8,21E-06	1,58E-05	7,96E-04	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	7,35E-08	2,09E-06	4,03E-06	1,26E-07	-2,90E-04
EP-marine	kg Ne	2,66E-02	2,31E-03	2,04E-03	3,10E-02	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	1,02E-04	2,94E-04	5,78E-04	4,66E-05	-6,62E-03
EP-terrestrial	mol Ne	1,69E+00	2,56E-02	2,22E-02	1,74E+00	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	1,12E-03	3,25E-03	6,33E-03	2,79E-04	-7,73E-02
POCP ("smog") ³⁾	kg NMVOCe	7,74E-02	7,32E-03	7,42E-03	9,22E-02	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	3,08E-04	9,99E-04	1,59E-03	9,94E-05	-2,80E-02
ADP-minerals & metals ⁴⁾	kg Sbe	1,17E-03	4,09E-06	6,13E-06	1,18E-03	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	1,13E-08	1,19E-06	8,32E-06	2,62E-08	-5,79E-05
ADP-fossil resources	MJ	3,68E+02	1,80E+01	3,99E+01	4,25E+02	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	2,99E-01	3,77E+00	1,46E+00	2,07E-01	-7,46E+01
Water use ⁵⁾	m ³ e depr.	1,51E+01	8,05E-02	2,46E-01	1,54E+01	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	8,03E-04	1,97E-02	1,76E-01	1,05E-03	-1,36E+00

1) GWP = Global Warming Potential; 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO₄e; 3) POCP = Photochemical ozone formation; 4) ADP = Abiotic depletion potential; 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Particulate matter	Incidence	4,34E-06	9,97E-08	1,96E-07	4,64E-06	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	6,18E-09	1,91E-08	1,42E-08	1,49E-09	-5,08E-07
Ionizing radiation ⁶⁾	kBq U235e	1,40E+00	9,33E-02	2,07E-01	1,70E+00	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	1,37E-03	2,04E-02	1,05E-02	9,80E-04	-1,26E-01
Ecotoxicity (freshwater)	CTUe	8,19E+02	1,46E+01	2,46E+01	8,59E+02	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	1,80E-01	3,27E+00	4,01E+01	2,32E-01	-2,03E+02
Human toxicity, cancer	CTUh	8,50E-08	4,90E-10	1,07E-09	8,66E-08	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	6,88E-12	1,14E-10	5,76E-10	5,89E-12	2,28E-08
Human tox. non-cancer	CTUh	5,71E-07	1,45E-08	2,01E-08	6,06E-07	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	1,30E-10	3,20E-09	2,28E-08	1,31E-10	-1,13E-07
SQP ⁷⁾	-	4,07E+01	1,18E+01	5,53E+00	5,81E+01	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	3,88E-02	2,27E+00	1,85E+00	4,78E-01	-4,27E+01

6) EN 15804+A2 disclaimer for ionizing radiation, human health. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator; 7) SQP = Land use related impacts/soil quality.

USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Renew. PER as energy ⁸⁾	MJ	1,53E+01	2,47E-01	3,18E+00	1,88E+01	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	1,71E-03	6,47E-02	1,60E-01	3,21E-03	-1,28E+01
Renew. PER as material	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Total use of renew. PER	MJ	1,53E+01	2,47E-01	3,18E+00	1,88E+01	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	1,71E-03	6,47E-02	1,60E-01	3,21E-03	-1,28E+01
Non-re. PER as energy	MJ	2,60E+02	1,80E+01	3,99E+01	3,18E+02	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	2,99E-01	3,77E+00	1,46E+00	2,07E-01	-7,47E+01
Non-re. PER as material	MJ	1,07E+02	0,00E+00	0,00E+00	1,07E+02	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	-8,57E+01	-2,14E+01	0,00E+00
Total use of non-re. PER	MJ	3,67E+02	1,80E+01	3,99E+01	4,25E+02	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	2,99E-01	3,77E+00	-8,42E+01	-2,12E+01	-7,47E+01
Secondary materials	kg	2,01E+00	6,15E-03	3,43E-03	2,02E+00	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	1,17E-04	1,55E-03	1,72E-03	6,34E-05	1,65E+00
Renew. secondary fuels	MJ	9,01E-04	6,27E-05	5,02E-05	1,01E-03	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	3,82E-07	1,79E-05	5,35E-05	2,26E-06	-2,98E-04
Non-ren. secondary fuels	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Use of net fresh water	m ³	3,59E-01	2,17E-03	1,21E-02	3,73E-01	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	1,81E-05	5,29E-04	2,28E-03	2,23E-04	-4,97E-02

8) PER = Primary energy resources.

END OF LIFE – WASTE

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Hazardous waste	kg	3,57E+00	2,04E-02	3,69E-02	3,63E+00	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	4,00E-04	4,90E-03	5,53E-03	0,00E+00	-1,33E+00
Non-hazardous waste	kg	2,35E+01	3,44E-01	6,27E-01	2,45E+01	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	2,81E-03	8,87E-02	2,39E+00	1,04E+00	-1,84E+01
Radioactive waste	kg	4,88E-04	1,24E-04	2,70E-04	8,82E-04	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	2,10E-06	2,57E-05	4,76E-06	0,00E+00	-1,28E-04

END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Components for re-use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Materials for recycling	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	2,74E+00	0,00E+00	0,00E+00
Materials for energy rec	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	2,22E+00	0,00E+00	0,00E+00
Exported energy	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	6,25E+01	0,00E+00	0,00E+00

ENVIRONMENTAL IMPACTS – EN 15804+A1, CML / ISO 21930

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Global Warming Pot.	kg CO ₂ e	2,00E+01	1,22E+00	3,12E+00	2,43E+01	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	2,20E-02	2,54E-01	7,10E+00	7,25E-02	-7,30E+00
Ozone depletion Pot.	kg CFC _{1,1} e	9,61E-07	2,23E-07	5,06E-07	1,69E-06	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	3,76E-09	4,58E-08	1,11E-08	2,23E-09	-4,10E-07
Acidification	kg SO ₂ e	2,53E-01	6,59E-03	2,12E-02	2,81E-01	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	1,64E-04	7,98E-04	1,24E-03	5,69E-05	-3,97E-02
Eutrophication	kg PO ₄ ³ e	6,87E-02	1,14E-03	1,54E-03	7,14E-02	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	3,81E-05	1,88E-04	7,76E-04	3,40E-03	-1,20E-02
POCP ("smog")	kg C ₂ H ₄ e	5,55E-03	2,22E-04	8,25E-04	6,60E-03	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	3,60E-06	3,37E-05	3,41E-05	1,34E-05	-2,96E-03
ADP-elements	kg Sbe	1,17E-03	4,00E-06	6,09E-06	1,18E-03	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	1,11E-08	1,17E-06	8,27E-06	2,54E-08	-5,77E-05
ADP-fossil	MJ	3,67E+02	1,80E+01	3,99E+01	4,25E+02	MND	0,00E+00	MND	MND	MND	MND	MND	MND	MND	2,99E-01	3,77E+00	1,46E+00	2,07E-01	-7,47E+01

ANNEX I – SCALING TABLE

Model	VTL5/2	VTL6/2	VTL7/2	VTL8/2	VTL9/2	VTL10/2	VTL11/2	VTL12/2	VTL13/2	VTL14/2	VTL15/2	VTL16/2	VTL18/2
Sf - Insulation Thickness	5 cm	6 cm	7 cm	8 cm	9 cm	10 cm	11 cm	12 cm	13 cm	14 cm	15 cm	16 cm	18 cm
Rd - Thermal resistance [m ² K/W]	1,62	1,95	2,28	2,62	2,95	3,28	3,62	3,95	4,28	4,62	4,95	5,28	5,95
Product Weight per 1 m ²	4,2 kg/m ²	4,4 kg/m ²	4,6 kg/m ²	4,8 kg/m ²	5,0 kg/m ²	5,2 kg/m ²	5,4 kg/m ²	5,6 kg/m ²	5,8 kg/m ²	6 kg/m ²	6,2 kg/m ²	6,4 kg/m ²	6,8 kg/m ²
HT - Sistem Thickness	7 cm	8 cm	9 cm	10 cm	11 cm	12 cm	13 cm	14 cm	15 cm	16 cm	17 cm	18 cm	20 cm
Rs - Thermal resistance [m ² K/W]	1,78	2,11	2,44	2,78	3,11	3,44	3,78	4,11	4,44	4,78	5,11	5,78	6,11
Impact Category	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3
GWP - total	0,63	0,67	0,71	0,75	0,80	0,84	0,88	0,92	0,96	1,00	1,04	1,08	1,16
GWP - fossil	0,63	0,67	0,71	0,75	0,80	0,84	0,88	0,92	0,96	1,00	1,04	1,08	1,16
GWP - biogenic	0,63	0,63	0,63	0,75	0,75	0,75	0,88	0,88	0,88	1,00	1,00	1,00	1,13
GWP - LULUC	1,00	1,00	1,00	1,00	1,00	1,00	1,00	1,00	1,00	1,00	1,00	1,00	1,00
Ozone depletion potential	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	1,00	0,00	0,00	0,00
Acidification potential	0,91	0,91	0,93	0,93	0,96	0,96	0,98	0,98	1,00	1,00	1,00	1,02	1,04
EP - freshwater	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	1,00	0,00	0,00	0,00
EP - marine	1,00	1,00	1,00	1,00	1,00	1,00	1,00	1,00	1,00	1,00	1,00	1,00	1,00
EP - terrestrial	0,97	0,97	0,97	0,98	0,98	0,98	0,99	0,99	0,99	1,00	1,00	1,01	1,01
POCP ("smog")	0,67	0,78	0,78	0,78	0,89	0,89	0,89	1,00	1,00	1,00	1,11	1,11	1,11
ADP - minerals & metals	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	1,00	0,00	0,00	0,00
ADP - fossil resources	0,57	0,62	0,67	0,72	0,76	0,81	0,86	0,91	0,95	1,00	1,05	1,09	1,19
Water use	0,66	0,70	0,74	0,77	0,81	0,85	0,89	0,92	0,96	1,00	1,04	1,08	1,15

Model	VTL20/2	VTL9/2M	VTL10/2M	VTL12/2M	VTL14/2M	VTL15/2M	VTL10/2STR	VTL11/2STR	VTL12/2STR	VTL13/2STR	VTL14/2STR	VTL15/2STR	VTL18/2STR	VTL20/2STR
Sf - Insulation Thickness	20 cm	9 cm	10 cm	12 cm	14 cm	15 cm	10 cm	11 cm	12 cm	13 cm	14 cm	15 cm	18 cm	20 cm
Rd - Thermal resistance [m ² K/W]	6,62	2,95	3,28	3,95	4,62	4,95	3,28	3,62	3,95	4,28	4,62	4,95	5,95	6,62
Product Weight per 1 m ²	7,2 kg/m ²	5,3 kg/m ²	5,5 kg/m ²	5,9 kg/m ²	6,3 kg/m ²	6,5 kg/m ²	5,5 kg/m ²	5,7 kg/m ²	5,9 kg/m ²	6,1 kg/m ²	6,3 kg/m ²	6,5 kg/m ²	7,1 kg/m ²	7,5 kg/m ²
HT - Sistem Thickness	22 cm	11 cm	12 cm	14 cm	16 cm	17 cm	12 cm	13 cm	14 cm	15 cm	16 cm	17 cm	20 cm	22 cm
Rs - Thermal resistance [m ² K/W]	6,78	3,11	3,44	4,11	4,78	5,11	3,44	3,78	4,11	4,44	4,78	5,11	6,11	6,78
Impact Category	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3	A1-A3
GWP - total	1,24	0,88	0,92	1,00	1,08	1,12	1,00	1,04	1,08	1,12	1,16	1,20	1,30	1,41
GWP - fossil	1,24	0,88	0,92	1,00	1,08	1,12	1,00	1,04	1,08	1,12	1,16	1,20	1,30	1,41
GWP - biogenic	1,25	0,88	0,88	1,00	1,00	1,13	1,00	1,00	1,00	1,13	1,13	1,13	1,25	1,38
GWP - LULUC	1,00	2,00	2,00	2,00	2,00	2,00	2,00	2,00	2,00	2,00	2,00	2,00	2,00	2,00
Ozone depletion potential	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00
Acidification potential	1,07	1,11	1,13	1,15	1,17	1,17	1,24	1,26	1,26	1,28	1,28	1,30	1,30	1,35
EP - freshwater	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00
EP - marine	1,00	1,00	1,00	1,00	1,33	1,33	1,33	1,33	1,33	1,33	1,33	1,33	1,33	1,33
EP - terrestrial	1,02	1,16	1,17	1,17	1,18	1,18	1,29	1,30	1,30	1,30	1,31	1,31	1,32	1,33
POCP ("smog")	1,22	1,00	1,00	1,11	1,11	1,11	1,11	1,11	1,11	1,22	1,22	1,22	1,33	1,44
ADP - minerals & metals	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00
ADP - fossil resources	1,28	0,83	0,87	0,97	1,06	1,11	0,93	0,98	1,03	1,08	1,12	1,17	1,29	1,41
Water use	1,23	0,90	0,94	1,01	1,09	1,13	1,01	1,05	1,09	1,13	1,17	1,20	1,31	1,39

HT = Spessore del sistema;

Sf = Spessore isolante;

Rd = Resistenza termica dello strato isolante;

Rs = Resistenza termica definita come la resistenza termica media ponderata delle resistenze (Ri) relativa ad ogni sezione (Si) caratterizzante il sistema posato in opera, escludendo dal calcolo le finiture ed il contributo degli strati liminari, $R = \sum Ri Si / \sum Si$.

VERIFICATION STATEMENT

VERIFICATION PROCESS FOR THIS EPD

This EPD has been verified in accordance with ISO 14025 by an independent, third-party verifier by reviewing results, documents and compliancy with reference standard, ISO 14025 and ISO 14040/14044, following the process and checklists of the program operator for:

- This Environmental Product Declaration
- The Life-Cycle Assessment used in this EPD
- The digital background data for this EPD

Why does verification transparency matter? [Read more online](#)

This EPD has been generated by One Click LCA EPD generator, which has been verified and approved by the EPD Hub.

THIRD-PARTY VERIFICATION STATEMENT

I hereby confirm that, following detailed examination, I have not established any relevant deviations by the studied Environmental Product Declaration (EPD), its LCA and project report, in terms of the data collected and used in the LCA calculations, the way the LCA-based calculations have been carried out, the presentation of environmental data in the EPD, and other additional environmental information, as present with respect to the procedural and methodological requirements in ISO 14025:2010 and reference standard.

I confirm that the company-specific data has been examined as regards plausibility and consistency; the declaration owner is responsible for its factual integrity and legal compliance.

I confirm that I have sufficient knowledge and experience of construction products, this specific product category, the construction industry, relevant standards, and the geographical area of the EPD to carry out this verification.

I confirm my independence in my role as verifier; I have not been involved in the execution of the LCA or in the development of the declaration and have no conflicts of interest regarding this verification.

HaiHa Nguyen, as an authorized verifier acting for EPD Hub Limited
15.02.2024

